



# DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



## 55x55x51 K 3.0

1. LEK no. KE 0062  
2. Model Inserts  
3. Intended use Insert for solid fuels without heating water  
4. Manufacturer Austroflamm GmbH  
Austroflamm-Platz 1  
A-4631 Krenglbach  
5. Representative -  
6. System(s) for assessing and verifying the constancy of performance of the construction product 3

Test laboratory identification number/test report number	1015 / 30-17198/3/T
Harmonized technical specification	EN 16510-2-2:2022
Load bearing capacity (kg)	NPD
Minimum distance to combustible materials - bottom dB [mm]	0
Minimum distance to combustible materials - floor in front dF [mm]	830
Minimum distance to combustible materials - distance to ceiling dC [mm]	750
Minimum distance to combustible materials - distance to rear dR [mm]	0
Minimum distance to combustible materials - left side dS_1 [mm]	0
Minimum distance to combustible materials - right side dS_2 [mm]	0
Minimum distance to combustible materials - left side radiation area dL_1 [mm]	450
Minimum distance to combustible materials - right side radiation area dL_2 [mm]	450
Minimum distance to adjacent combustible materials (e.g. furniture) dP [mm]	800
Material type and material thickness of the thermal insulation	Calcium silicate Promasil 950KS
CO at 13% O <sub>2</sub> at nominal heat output [mg/Nm <sup>3</sup> ]	≤1500
NOX at 13% O <sub>2</sub> at nominal heat output [mg/Nm <sup>3</sup> ]	≤200
OGC at 13% O <sub>2</sub> at nominal heat output [mg/Nm <sup>3</sup> ]	≤120
Particulate matter (PM) at 13% O <sub>2</sub> at nominal heat output [mg/Nm <sup>3</sup> ]	≤40
CO at 13% O <sub>2</sub> at part load heat output [mg/Nm <sup>3</sup> ]	NPD
NOX at 13% O <sub>2</sub> at part load heat output [mg/Nm <sup>3</sup> ]	NPD
OGC at 13% O <sub>2</sub> at part load heat output [mg/Nm <sup>3</sup> ]	NPD
Particulate matter (PM) at 13% O <sub>2</sub> at part load heat output [mg/Nm <sup>3</sup> ]	NPD
Flue gas temperature at the nozzle at nominal heat output [°C]	295
Minimum delivery pressure at nominal heat output [Pa]	12
Flue gas mass flow at nominal heat output [g/s]	11.5
Flue gas temperature at part load heat output [°C]	NPD
Minimum flue draught at part load heat output [Pa]	NPD



# DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



## 55x55x51 K 3.0

1. LEK no.	KE 0062
2. Model	Inserts
3. Intended use	Insert for solid fuels without heating water
4. Manufacturer	Austroflamm GmbH Austroflamm-Platz 1 A-4631 Krenglbach
5. Representative	-
6. System(s) for assessing and verifying the constancy of performance of the construction product	3

Flue gas mass flow at part load heat output [g/s]	NPD
Fire safety for installation to the chimney	T400 G
Nominal room heat output [kW]	11.3
Nominal water heat output [kW]	NPD
Efficiency at nominal heat output [%]	80.5
Partial load room heat output [kW]	NPD
Partial load water heat output [kW]	NPD
Efficiency at part load heat output [%]	NPD
Space heating annual use efficiency [%]	70
Energy efficiency index (EEI)	106
Energy efficiency class	A
Auxiliary power consumption at nominal heat output [kW]	NPD
Auxiliary power consumption at minimum heat output [kW]	NPD
Auxiliary power consumption in standby condition [kW]	NPD
Environmental sustainability	NPD

The performance of the aforementioned product corresponds to the declared performance(s). The above-mentioned manufacturer is solely responsible for the preparation of this declaration of performance in accordance with Regulation (EU) No. 305/2011.

Krenglbach, 21/01/2026

Andreas Schönfeld  
Managing Director