DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011

AUSTROFLAMM

75x39-K-2.0

1. LEK no.	KE 0018
2. Model	Inserts
3. Intended use	Insert for solid fuels without heating water
4. Manufacturer	Austroflamm GmbH Austroflamm-Platz 1 A-4631 Krenglbach
5. Representative	-
6. System(s) for assessing and verifying the constancy of performance of the construction product	3

Test laboratory identification number/test report number	1015 / 1015-CPR-30-17198/4/TZ
Harmonized technical specification	EN 16510-2-2:2022
Load bearing capacity (kg)	NPD
Minimum distance to combustible materials – bottom dB [mm]	0
Minimum distance to combustible materials – floor in front dF [mm]	1030
Minimum distance to combustible materials – distance to ceiling dC [mm]	750
Minimum distance to combustible materials - distance to rear dR [mm]	0
Minimum distance to combustible materials – left side dS_1 [mm]	0
Minimum distance to combustible materials – right side dS_2 [mm]	0
Minimum distance to combustible materials – left side radiation area dL_1 [mm]	300
Minimum distance to combustible materials – right side radiation area dL_2 [mm]	300
Minimum distance to adjacent combustible materials (e.g. furniture) dP [mm]	1500
Material type and material thickness of the thermal insulation	Calcium silicate Promasil 950KS
CO at 13% O2 at nominal heat output [mg/Nm³]	≤1250
NOX at 13% O2 at nominal heat output [mg/Nm³]	≤160
OGC at 13% O2 at nominal heat output [mg/Nm³]	≤70
Particulate matter (PM) at 13% O2 at nominal heat output [mg/Nm³]	≤30
CO at 13% O2 at part load heat output [mg/Nm³]	NPD
NOX at 13% O2 at part load heat output [mg/Nm³]	NPD
OGC at 13% O2 at part load heat output [mg/Nm³]	NPD
Particulate matter (PM) at 13% O2 at part load heat output [mg/Nm³]	NPD
Flue gas temperature at the nozzle at nominal heat output [°C]	312
Minimum delivery pressure at nominal heat output [Pa]	11
Flue gas mass flow at nominal heat output [g/s]	10.5
Flue gas temperature at part load heat output [°C]	NPD

DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011

AUSTROFLAMM

75x39-K-2.0

1. LEK no.	KE 0018
2. Model	Inserts
3. Intended use	Insert for solid fuels without heating water
4. Manufacturer	Austroflamm GmbH Austroflamm-Platz 1 A-4631 Krenglbach
5. Representative	-
6. System(s) for assessing and verifying the constancy of performance of the construction product	3

Minimum flue draught at part load heat output [Pa]	NPD
Flue gas mass flow at part load heat output [g/s]	NPD
Fire safety for installation to the chimney	T400 G
Nominal room heat output [kW]	10.0
Nominal water heat output [kW]	NPD
Efficiency at nominal heat output [%]	78
Partial load room heat output [kW]	NPD
Partial load water heat output [kW]	NPD
Efficiency at at part load heat output [%]	NPD
Space heating annual use efficiency [%]	68
Energy efficiency index (EEI)	103
Energy efficiency class	A
Auxiliary power consumption at nominal heat output [kW]	NPD
Auxiliary power consumption at minimum heat output [kW]	NPD
Auxiliary power consumption in standby condition [kW]	NPD
Environmental sustainability	NPD

The performance of the aforementioned product corresponds to the declared performance(s). The above-mentioned manufacturer is solely responsible for the preparation of this declaration of performance in accordance with Regulation (EU) No. 305/2011.

Krenglbach, 06/10/2026

Andreas Schönfeld
Managing Director