



DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



75x39-SII-2.0

1. LEK no.	KE 0030
2. Model	Inserts
3. Intended use	Insert for solid fuels without heating water
4. Manufacturer	Austroflamm GmbH Austroflamm-Platz 1 A-4631 Krenglbach
5. Representative	-
6. System(s) for assessing and verifying the constancy of performance of the construction product	3

Test laboratory identification number/test report number	1625 / RRF - 29 15 3852
Harmonized technical specification	EN 13229:2001/A:2004/AC:2007
Load bearing capacity (kg)	-
Minimum distance to combustible materials - bottom dB [mm]	0
Minimum distance to combustible materials - floor in front dF [mm]	-
Minimum distance to combustible materials - distance to ceiling dC [mm]	750
Minimum distance to combustible materials - distance to rear dR [mm]	800
Minimum distance to combustible materials - left side dS_1 [mm]	0
Minimum distance to combustible materials - right side dS_2 [mm]	0
Minimum distance to combustible materials - left side radiation area dL_1 [mm]	-
Minimum distance to combustible materials - right side radiation area dL_2 [mm]	-
Minimum distance to adjacent combustible materials (e.g. furniture) dP [mm]	800
Material type and material thickness of the thermal insulation	Calcium silicate Promasil 950KS
CO at 13% O ₂ at nominal heat output [mg/Nm ³]	≤ 1250
NOX at 13% O ₂ at nominal heat output [mg/Nm ³]	≤ 160
OGC at 13% O ₂ at nominal heat output [mg/Nm ³]	≤ 81
Particulate matter (PM) at 13% O ₂ at nominal heat output [mg/Nm ³]	≤ 30
CO at 13% O ₂ at part load heat output [mg/Nm ³]	-
NOX at 13% O ₂ at part load heat output [mg/Nm ³]	-
OGC at 13% O ₂ at part load heat output [mg/Nm ³]	-
Particulate matter (PM) at 13% O ₂ at part load heat output [mg/Nm ³]	-
Flue gas temperature at the nozzle at nominal heat output [°C]	286
Minimum delivery pressure at nominal heat output [Pa]	12
Flue gas mass flow at nominal heat output [g/s]	7.3
Flue gas temperature at part load heat output [°C]	-



DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



75x39-SII-2.0

1. LEK no.	KE 0030
2. Model	Inserts
3. Intended use	Insert for solid fuels without heating water
4. Manufacturer	Austroflamm GmbH Austroflamm-Platz 1 A-4631 Krenglbach
5. Representative	-
6. System(s) for assessing and verifying the constancy of performance of the construction product	3

Minimum flue draught at part load heat output [Pa]	-
Flue gas mass flow at part load heat output [g/s]	-
Fire safety for installation to the chimney	T400 G
Nominal room heat output [kW]	10.0
Nominal water heat output [kW]	-
Efficiency at nominal heat output [%]	82
Partial load room heat output [kW]	-
Partial load water heat output [kW]	-
Efficiency at at part load heat output [%]	-
Space heating annual use efficiency [%]	72
Energy efficiency index (EEI)	108
Energy efficiency class	A+
Auxiliary power consumption at nominal heat output [kW]	-
Auxiliary power consumption at minimum heat output [kW]	-
Auxiliary power consumption in standby condition [kW]	-
Environmental sustainability	NPD

The performance of the aforementioned product corresponds to the declared performance(s). The above-mentioned manufacturer is solely responsible for the preparation of this declaration of performance in accordance with Regulation (EU) No. 305/2011.

Krenglbach, 14/10/2025


Andreas Schönfeld
Managing Director