ϵ

DECLARATION OF PERFORMANCE

AUSTROFLAMM

as per Regulation (EC) 305/2011

Bono Xtra

 1. LEK no.
 KO 0002

 2. Model
 Stove

3. Intended use Space heater for solid fuels without heating water

4. ManufacturerAustroflamm GmbH
Austroflamm-Platz 1

A-4631 Krenglbach

5. Representative6. System for verifying constancy of per-

formance

	Bono Xtra
Notified Body/ name of test laboratory	RRF
Test laboratory identification number/test report number	1625 / RRF - 40 11 2750
Harmonized technical specification	EN 13240:2001/A2:2004/ AC:2007
Fire safety	fulfilled
Reaction to fire	A1 as per EN 13501-1
Minimum distance to combustible materials - distance to rear dR [mm]	160
Minimum distance to combustible materials - left side dS_1 [mm]	270
Minimum distance to combustible materials - right side dS_2 [mm]	270
Minimum distance to combustible materials - distance to ceiling dC [mm]	750
Minimum distance to adjacent combustible materials (e.g. furniture) dP [mm]	900
Minimum distance to combustible materials - bottom dB [mm]	0
Fire hazard through burning firewood falling out of the stove	fulfilled
Cleanability	fulfilled
Emission of combustion products	fulfilled
Emission (CO) of combustion products at nominal heat output [%]	0.08
Emission (CO) of combustion products at reduced heat output [%]	-
Flue gas temperature in the measuring section at nominal heat output [°C]	282
Flue gas temperature at the nozzle at nominal heat output [°C]	322
Surface temperature	fulfilled
Electrical safety	-
Release of hazardous substances	NPD
Maximum operating pressure [bar]	-
Maximum operating pressure option	not relevant
Mechanical strength (for supporting a chimney)	NPD
Heat output / energy efficiency	fulfilled



DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



Bono Xtra

 1. LEK no.
 KO 0002

 2. Model
 Stove

3. Intended use Space heater for solid fuels without heating water

4. Manufacturer

Austroflamm GmbH

Austroflamm-Platz 1

A-4631 Krenglbach

5. Representative6. System for verifying constancy of per-

formance

	Bono Xtra
Nominal heat efficiency [kW]	5.0
Nominal room heat output [kW]	5.0
Nominal water heat output [kW]	-
Efficiency at nominal heat output [%]	80.1

The performance of the product under numbers 1 and 2 corresponds to the declared performance. The manufacturer alone is responsible for the production of this declaration of performance under number 4. Signed for the manufacturer and on behalf of the manufacturer by:

Krenglbach, 26/09/2025

Doris Pfeiffer Managing Director