



DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



Elisabeth Type 1 / Elisabeth Type 2

1. LEK no.	KO 0069
2. Model	Stove
3. Intended use	Space heating in residential buildings
4. Manufacturer	Austroflamm GmbH Austroflamm-Platz 1 A-4631 Krenglbach
5. Representative	-
6. System(s) for assessing and verifying the constancy of performance of the construction product	3

Test laboratory identification number/test report number	0051 / CS24-0110630-01
Harmonized technical specification	EN 16510-2-1:2022
Load bearing capacity (kg)	70/70
Minimum distance to combustible materials - bottom dB [mm]	0/0
Minimum distance to combustible materials - floor in front dF [mm]	600/600
Minimum distance to combustible materials - distance to ceiling dC [mm]	750/750
Minimum distance to combustible materials - distance to rear dR [mm]	250/250
Minimum distance to combustible materials - left side dS_1 [mm]	250/250
Minimum distance to combustible materials - right side dS_2 [mm]	250/250
Minimum distance to combustible materials - left side radiation area dL_1 [mm]	600/600
Minimum distance to combustible materials - right side radiation area dL_2 [mm]	600/600
Minimum distance to adjacent combustible materials (e.g. furniture) dP [mm]	1300/1300
Material type and material thickness of the thermal insulation	-/-
CO at 13% O ₂ at nominal heat output [mg/Nm ³]	≤ 1250/620
NOX at 13% O ₂ at nominal heat output [mg/Nm ³]	≤ 160/86
OGC at 13% O ₂ at nominal heat output [mg/Nm ³]	≤ 70/28
Particulate matter (PM) at 13% O ₂ at nominal heat output [mg/Nm ³]	≤ 30/9
CO at 13% O ₂ at part load heat output [mg/Nm ³]	-/-
NOX at 13% O ₂ at part load heat output [mg/Nm ³]	-/-
OGC at 13% O ₂ at part load heat output [mg/Nm ³]	-/-
Particulate matter (PM) at 13% O ₂ at part load heat output [mg/Nm ³]	-/-
Flue gas temperature at the nozzle at nominal heat output [°C]	299 / 200
Minimum delivery pressure at nominal heat output [Pa]	12/12
Flue gas mass flow at nominal heat output [g/s]	5.0 / 6.5
Flue gas temperature at part load heat output [°C]	-/-
Minimum flue draught at part load heat output [Pa]	-/-



DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



Elisabeth Type 1 / Elisabeth Type 2

1. LEK no. KO 0069
2. Model Stove
3. Intended use Space heating in residential buildings
4. Manufacturer Austroflamm GmbH
Austroflamm-Platz 1
A-4631 Krenglbach
5. Representative -
6. System(s) for assessing and verifying the constancy of performance of the construction product 3

Flue gas mass flow at part load heat output [g/s]	-/-
Fire safety for installation to the chimney	T400 G/T400 G
Nominal room heat output [kW]	7.0 / 7.2
Nominal water heat output [kW]	-/-
Efficiency at nominal heat output [%]	86 / 86.9
Partial load room heat output [kW]	-/-
Partial load water heat output [kW]	-/-
Efficiency at at part load heat output [%]	-/-
Space heating annual use efficiency [%]	76 / 76.9
Energy efficiency index (EEI)	114 / 116
Energy efficiency class	A+/A+
Auxiliary power consumption at nominal heat output [kW]	-/-
Auxiliary power consumption at minimum heat output [kW]	-/-
Auxiliary power consumption in standby condition [kW]	-/-
Environmental sustainability	NPD

The performance of the aforementioned product corresponds to the declared performance(s). The above-mentioned manufacturer is solely responsible for the preparation of this declaration of performance in accordance with Regulation (EU) No. 305/2011.

Krenglbach, 26/09/2025

Andreas Schönfeld
Managing Director