ϵ

DECLARATION OF PERFORMANCE

AUSTROFLAMM

as per Regulation (EC) 305/2011

Jini Xtra

 1. LEK no.
 KO 0030

 2. Model
 Stove

3. Intended use Space heating in residential buildings

4. ManufacturerAustroflamm GmbH
Austroflamm-Platz 1

A-4631 Krenglbach

5. Representative

6. System(s) for assessing and verifying the 3 constancy of performance of the construction product

| | Jini-Xtra |
|---|-----------------------------------|
| Notified Body/ name of test laboratory | RRF |
| Test laboratory identification number/test report number | 1625 / RRF - 40 13 3340 |
| Harmonized technical specification | EN 13240:2001/A2:2004/ AC:2007 |
| Fire safety | fulfilled |
| Reaction to fire | A1 as per EN 13501-1 |
| Minimum distance to combustible materials - distance to rear dR [mm] | 160 |
| Minimum distance to combustible materials - left side dS_1 [mm] | 270 |
| Minimum distance to combustible materials - right side dS_2 [mm] | 270 |
| Minimum distance to combustible materials - distance to ceiling dC [mm] | 750 |
| Minimum distance to adjacent combustible materials (e.g. furniture) dP [mm] | 1000 |
| Minimum distance to combustible materials - bottom dB [mm] | 0 |
| Fire hazard through burning firewood falling out of the stove | fulfilled |
| Cleanability | fulfilled |
| Emission of combustion products | fulfilled |
| Emission (CO) of combustion products at nominal heat output [%] | 0.10 |
| Emission (CO) of combustion products at reduced heat output [%] | - |
| Flue gas temperature in the measuring section at nominal heat output [°C] | 232 |
| Flue gas temperature at the nozzle at nominal heat output [°C] | 343 |
| Surface temperature | fulfilled |
| Electrical safety | - |
| Release of hazardous substances | NPD |
| Maximum operating pressure [bar] | - |
| Maximum operating pressure option | not relevant |
| Mechanical strength (for supporting a chimney) | NPD |
| Heat output / energy efficiency | fulfilled |



DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



Jini Xtra

 1. LEK no.
 KO 0030

 2. Model
 Stove

3. Intended use Space heating in residential buildings

4. Manufacturer

Austroflamm GmbH

Austroflamm-Platz 1

A-4631 Krenglbach

5. Representative

6. System(s) for assessing and verifying the 3 constancy of performance of the construction product

| | Jini-Xtra |
|---------------------------------------|-----------|
| Nominal heat efficiency [kW] | 4.0 |
| Nominal room heat output [kW] | 4.0 |
| Nominal water heat output [kW] | - |
| Efficiency at nominal heat output [%] | 80.9 |

The performance of the aforementioned product corresponds to the declared performance(s). The above-mentioned manufacturer is solely responsible for the preparation of this declaration of performance in accordance with Regulation (EU) No. 305/2011.

Krenglbach, 26/09/2025

Andreas Schönfeld Managing Director