



DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



Kamiba 59 K2 R

1. LEK no.	KO 0078
2. Model	Stove
3. Intended use	Space heating in residential buildings
4. Manufacturer	Austroflamm GmbH Austroflamm-Platz 1 A-4631 Krenglbach
5. Representative	-
6. System(s) for assessing and verifying the constancy of performance of the construction product	3

Test laboratory identification number/test report number	1721 / F 26/01/1224
Harmonized technical specification	EN 16510-2-1:2022
Load bearing capacity (kg)	70
Minimum distance to combustible materials - bottom dB [mm]	20
Minimum distance to combustible materials - floor in front dF [mm]	0
Minimum distance to combustible materials - distance to ceiling dC [mm]	750
Minimum distance to combustible materials - distance to rear dR [mm]	150
Minimum distance to combustible materials - left side dS_1 [mm]	180
Minimum distance to combustible materials - right side dS_2 [mm]	180
Minimum distance to combustible materials - left side radiation area dL_1 [mm]	0
Minimum distance to combustible materials - right side radiation area dL_2 [mm]	0
Minimum distance to adjacent combustible materials (e.g. furniture) dP [mm]	1100
Material type and material thickness of the thermal insulation	NPD
CO at 13% O ₂ at nominal heat output [mg/Nm ³]	≤1500
NOX at 13% O ₂ at nominal heat output [mg/Nm ³]	≤200
OGC at 13% O ₂ at nominal heat output [mg/Nm ³]	≤120
Particulate matter (PM) at 13% O ₂ at nominal heat output [mg/Nm ³]	≤40
CO at 13% O ₂ at part load heat output [mg/Nm ³]	NPD
NOX at 13% O ₂ at part load heat output [mg/Nm ³]	NPD
OGC at 13% O ₂ at part load heat output [mg/Nm ³]	NPD
Particulate matter (PM) at 13% O ₂ at part load heat output [mg/Nm ³]	NPD
Flue gas temperature at the nozzle at nominal heat output [°C]	233
Minimum delivery pressure at nominal heat output [Pa]	13
Flue gas mass flow at nominal heat output [g/s]	8.0
Flue gas temperature at part load heat output [°C]	NPD
Minimum flue draught at part load heat output [Pa]	NPD



DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



Kamiba 59 K2 R

1. LEK no.	KO 0078
2. Model	Stove
3. Intended use	Space heating in residential buildings
4. Manufacturer	Austroflamm GmbH Austroflamm-Platz 1 A-4631 Krenglbach
5. Representative	-
6. System(s) for assessing and verifying the constancy of performance of the construction product	3

Flue gas mass flow at part load heat output [g/s]	NPD
Fire safety for installation to the chimney	T400-G
Nominal room heat output [kW]	7.0
Nominal water heat output [kW]	NPD
Efficiency at nominal heat output [%]	82
Partial load room heat output [kW]	NPD
Partial load water heat output [kW]	NPD
Efficiency at at part load heat output [%]	NPD
Space heating annual use efficiency [%]	72
Energy efficiency index (EEI)	108
Energy efficiency class	A+
Auxiliary power consumption at nominal heat output [kW]	NPD
Auxiliary power consumption at minimum heat output [kW]	NPD
Auxiliary power consumption in standby condition [kW]	NPD
Environmental sustainability	NPD

The performance of the aforementioned product corresponds to the declared performance(s). The above-mentioned manufacturer is solely responsible for the preparation of this declaration of performance in accordance with Regulation (EU) No. 305/2011.

Krenglbach, 26/03/2026

Andreas Schönfeld
Managing Director