# DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011

AUSTROFLAMM

## Koko Xtra 2.0 Type 1 / Type 2

| | |
|---|---|
| **1. LEK no.** | KO 0012 |
| **2. Model** | Stove |
| **3. Intended use** | Space heating in residential buildings |
| **4. Manufacturer** | Austroflamm GmbH<br>Austroflamm-Platz 1<br>A-4631 Krenglbach |
| **5. Representative** | - |
| **6. System(s) for assessing and verifying the constancy of performance of the construction product** | 3 |

| | |
|---|---|
| Test laboratory identification number/test report number | 0051 / CS25-00118853-01 |
| Harmonized technical specification | EN 16510-2-1:2022 |
| Load bearing capacity (kg) | 70/70 |
| Minimum distance to combustible materials – bottom dB [mm] | 0/0 |
| Minimum distance to combustible materials – floor in front dF [mm] | 0/0 |
| Minimum distance to combustible materials – distance to ceiling dC [mm] | 750/750 |
| Minimum distance to combustible materials - distance to rear dR [mm] | 200/200 |
| Minimum distance to combustible materials – left side dS_1 [mm] | 350/350 |
| Minimum distance to combustible materials – right side dS_2 [mm] | 350/350 |
| Minimum distance to combustible materials – left side radiation area dL_1 [mm] | 600/600 |
| Minimum distance to combustible materials – right side radiation area dL_2 [mm] | 600/600 |
| Minimum distance to adjacent combustible materials (e.g. furniture) dP [mm] | 1300/1300 |
| Material type and material thickness of the thermal insulation | - |
| CO at 13% O2 at nominal heat output [mg/Nm³] | ≤ 1500/577 |
| NOX at 13% O2 at nominal heat output [mg/Nm³] | ≤ 200/87 |
| OGC at 13% O2 at nominal heat output [mg/Nm³] | ≤ 120/23 |
| Particulate matter (PM) at 13% O2 at nominal heat output [mg/Nm³] | ≤ 40/25 |
| CO at 13% O2 at part load heat output [mg/Nm³] | - |
| NOX at 13% O2 at part load heat output [mg/Nm³] | - |
| OGC at 13% O2 at part load heat output [mg/Nm³] | - |
| Particulate matter (PM) at 13% O2 at part load heat output [mg/Nm³] | - |
| Flue gas temperature at the nozzle at nominal heat output [°C] | 310/223 |
| Minimum delivery pressure at nominal heat output [Pa] | 13/12 |
| Flue gas mass flow at nominal heat output [g/s] | 6.3/6.5 |
| Flue gas temperature at part load heat output [°C] | - |
| Minimum flue draught at part load heat output [Pa] | - |

# DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011

## Koko Xtra 2.0 Type 1 / Type 2

| | |
|---|---|
| **1. LEK no.** | KO 0012 |
| **2. Model** | Stove |
| **3. Intended use** | Space heating in residential buildings |
| **4. Manufacturer** | Austroflamm GmbH<br>Austroflamm-Platz 1<br>A-4631 Krenglbach |
| **5. Representative** | - |
| **6. System(s) for assessing and verifying the constancy of performance of the construction product** | 3 |

| | |
|---|---|
| Flue gas mass flow at part load heat output [g/s] | - |
| Fire safety for installation to the chimney | T400G/T400G |
| Nominal room heat output [kW] | 7.5/8.2 |
| Nominal water heat output [kW] | - |
| Efficiency at nominal heat output [%] | 82/88.1 |
| Partial load room heat output [kW] | - |
| Partial load water heat output [kW] | - |
| Efficiency at at part load heat output [%] | - |
| Space heating annual use efficiency [%] | 72/ 78 |
| Energy efficiency index (EEI) | 109/ 118 |
| Energy efficiency class | A+/A+ |
| Auxiliary power consumption at nominal heat output [kW] | - |
| Auxiliary power consumption at minimum heat output [kW] | - |
| Auxiliary power consumption in standby condition [kW] | - |
| Environmental sustainability | NPD |

**The performance of the aforementioned product corresponds to the declared performance(s). The above-mentioned manufacturer is solely responsible for the preparation of this declaration of performance in accordance with Regulation (EU) No. 305/2011.**

Krenglbach, 26/09/2025

Andreas Schönfeld
Managing Director