



DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



Kylie Xtra 2.0 Type 1/Type 2

1. LEK no.	KO 0055
2. Model	Stove
3. Intended use	Space heating in residential buildings
4. Manufacturer	Austroflam GmbH Austroflam-Platz 1 A-4631 Krenglbach
5. Representative	-
6. System(s) for assessing and verifying the constancy of performance of the construction product	3

Test laboratory identification number/test report number	1721 / DBI F 25/07/1185
Harmonized technical specification	EN 16510-2-1:2022
Load bearing capacity (kg)	70/70
Minimum distance to combustible materials - bottom dB [mm]	0/ 0
Minimum distance to combustible materials - floor in front dF [mm]	800/ 800
Minimum distance to combustible materials - distance to ceiling dC [mm]	750/ 750
Minimum distance to combustible materials - distance to rear dR [mm]	100/ 100
Minimum distance to combustible materials - left side dS_1 [mm]	100/ 100
Minimum distance to combustible materials - right side dS_2 [mm]	100/ 100
Minimum distance to combustible materials - left side radiation area dL_1 [mm]	100/ 100
Minimum distance to combustible materials - right side radiation area dL_2 [mm]	100/ 100
Minimum distance to adjacent combustible materials (e.g. furniture) dP [mm]	800/ 800
Material type and material thickness of the thermal insulation	NPD/NPD
CO at 13% O ₂ at nominal heat output [mg/Nm ³]	≤ 1500/889
NOX at 13% O ₂ at nominal heat output [mg/Nm ³]	≤ 200/107
OGC at 13% O ₂ at nominal heat output [mg/Nm ³]	≤ 120/54
Particulate matter (PM) at 13% O ₂ at nominal heat output [mg/Nm ³]	≤ 40/39
CO at 13% O ₂ at part load heat output [mg/Nm ³]	NPD/NPD
NOX at 13% O ₂ at part load heat output [mg/Nm ³]	NPD/NPD
OGC at 13% O ₂ at part load heat output [mg/Nm ³]	NPD/NPD
Particulate matter (PM) at 13% O ₂ at part load heat output [mg/Nm ³]	NPD/NPD
Flue gas temperature at the nozzle at nominal heat output [°C]	297/ 239
Minimum delivery pressure at nominal heat output [Pa]	12/ 12
Flue gas mass flow at nominal heat output [g/s]	4.8/ 5.3
Flue gas temperature at part load heat output [°C]	NPD/NPD
Minimum flue draught at part load heat output [Pa]	NPD/NPD



DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



Kylie Xtra 2.0 Type 1/Type 2

1. LEK no.	KO 0055
2. Model	Stove
3. Intended use	Space heating in residential buildings
4. Manufacturer	Austroflamm GmbH Austroflamm-Platz 1 A-4631 Krenglbach
5. Representative	-
6. System(s) for assessing and verifying the constancy of performance of the construction product	3

Flue gas mass flow at part load heat output [g/s]	NPD/NPD
Fire safety for installation to the chimney	T400 G/T400 G
Nominal room heat output [kW]	7.4/ 7.4
Nominal water heat output [kW]	NPD/NPD
Efficiency at nominal heat output [%]	83/ 85
Partial load room heat output [kW]	NPD/NPD
Partial load water heat output [kW]	NPD/NPD
Efficiency at at part load heat output [%]	NPD/NPD
Space heating annual use efficiency [%]	73/ 75
Energy efficiency index (EEI)	110/ 113
Energy efficiency class	A+/A+
Auxiliary power consumption at nominal heat output [kW]	NPD/NPD
Auxiliary power consumption at minimum heat output [kW]	NPD/NPD
Auxiliary power consumption in standby condition [kW]	NPD/NPD
Environmental sustainability	NPD/NPD

The performance of the aforementioned product corresponds to the declared performance(s). The above-mentioned manufacturer is solely responsible for the preparation of this declaration of performance in accordance with Regulation (EU) No. 305/2011.

Krenglbach, 05/02/2026


Andreas Schönfeld
Managing Director