ϵ

DECLARATION OF PERFORMANCE

AUSTROFLAMM

as per Regulation (EC) 305/2011

Polly light

1. LEK no. PE 00032. Model Pellet stove

3. Intended use Space heating in residential buildings and, where applicable,

cooking

4. Manufacturer Austroflamm GmbH

Austroflamm-Platz 1 A-4631 Krenglbach

5. Representative

6. System(s) for assessing and verifying the 3 constancy of performance of the construc-

tion product

Notified Body/ name of test laboratory	DBI
Test laboratory identification number/test report number	1721 / F 16/11/0420
Harmonized technical specification	EN 14785:2006
Fire safety	fulfilled
Reaction to fire	A1
Minimum distance to combustible materials - distance to rear dR [mm]	100
Minimum distance to combustible materials - left side dS_1 [mm]	200
Minimum distance to combustible materials - right side dS_2 [mm]	200
Minimum distance to combustible materials - distance to ceiling dC [mm]	750
Minimum distance to adjacent combustible materials (e.g. furniture) dP [mm]	800
Minimum distance to combustible materials - bottom dB [mm]	0
Fire hazard through burning firewood falling out of the stove	fulfilled
Cleanability	fulfilled
Emission of combustion products	fulfilled
Emission (CO) of combustion products at nominal heat output [%]	0.002
Emission (CO) of combustion products at reduced heat output [%]	0.020
Flue gas temperature in the measuring section at nominal heat output [°C]	174
Flue gas temperature at the nozzle at nominal heat output [°C]	205
Surface temperature	fulfilled
Electrical safety	fulfilled
Release of hazardous substances	NPD
Maximum operating pressure [bar]	-
Maximum operating pressure option	-
Mechanical strength (for supporting a chimney)	NPD
Heat output / energy efficiency	fulfilled
Nominal heat efficiency [kW]	9.0



DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



Polly light

1. LEK no. PE 0003 2. Model Pellet stove

3. Intended use Space heating in residential buildings and, where applicable,

4. Manufacturer Austroflamm GmbH

> Austroflamm-Platz 1 A-4631 Krenglbach

5. Representative

constancy of performance of the construc-

6. System(s) for assessing and verifying the 3 tion product

Efficiency at part load heat output [%]	90
Nominal room heat output [kW]	9.0
Partial load room heat output [kW]	2.7
Nominal water heat output [kW]	-
Partial load water heat output [kW]	-
Efficiency at nominal heat output [%]	90
Efficiency at part load heat output [%]	90
Durability	NPD

The performance of the aforementioned product corresponds to the declared performance(s). The above-mentioned manufacturer is solely responsible for the preparation of this declaration of performance in accordance with Regulation (EU) No. 305/2011.

Krenglbach, 9/29/2025

Andreas Schönfeld Managing Director