CE

DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



Polly light

- 1. LEK no.
- 2. Model
- 3. Intended use
- 4. Manufacturer

PE 0003 Pellet stove Space heater for burning wood pellets without heating water Austroflamm GmbH Austroflamm-Platz 1 A-4631 Krenglbach

5. Representative

6. System for verifying constancy of perfor- 3 mance

	Polly-light
Notified Body/ name of test laboratory	DBI
Test laboratory identification number/test report number	1721 / F 16/11/0420
Harmonized technical specification	EN 14785:2006
Fire safety	fulfilled
Reaction to fire	A1
dR Distance rear [mm]	100
dS1 Distance left [mm]	200
dS2 Distance right [mm]	200
dC Distance above [mm]	750
dP Radiation front [mm]	800
dB Distance bottom [mm]	0
Fire hazard through burning firewood falling out of the stove	fulfilled
Cleanability	fulfilled
Emission of combustion products	fulfilled
Emission (CO) of combustion products at nominal heat output [%]	0.002
Emission (CO) of combustion products at reduced heat output [%]	0.020
Flue gas temperature in the measuring section at nominal heat output [°C]	174
Flue gas temperature at the nozzle at nominal heat output [°C]	205
Surface temperature	fulfilled
Electrical safety	fulfilled
Release of hazardous substances	NPD
Maximum operating pressure [bar]	-
Maximum operating pressure option	-
Mechanical strength (for supporting a chimney)	NPD
Heat output / energy efficiency	fulfilled

CE

DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



Polly light

1. LEK no.	PE 0003
2. Model	Pellet stove
3. Intended use	Space heater for burning wood pellets without heating water
4. Manufacturer	Austroflamm GmbH Austroflamm-Platz 1 A-4631 Krenglbach
5. Representative	-
6 System for varifying constance of partor	2

6. System for verifying constancy of perfor- 3 mance

	Polly-light
Nominal heat efficiency [kW]	9.0
Efficiency, partial output [%]	90
Nominal room heat output [kW]	9.0
Partial load room heat output [kW]	2.7
Nominal water heat output [kW]	-
Partial load water heat output [kW]	-
Efficiency / thermal efficiency / fuel energy efficiency at nominal heat efficiency [%]	90
Efficiency, partial output [%]	90
Durability	NPD

The performance of the product under numbers 1 and 2 corresponds to the declared performance. The manufacturer alone is responsible for the production of this declaration of performance under number 4. Signed for the manufacturer and on behalf of the manufacturer by:

Doris Pfeiffer Managing Director

Krenglbach, 2/6/2025