



DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



Slim 4.0 left Type 1 / Type 2

1. LEK no.	KO 0067
2. Model	Stove
3. Intended use	Space heating in residential buildings
4. Manufacturer	Austroflamm GmbH Austroflamm-Platz 1 A-4631 Krenglbach
5. Representative	-
6. System(s) for assessing and verifying the constancy of performance of the construction product	3

Test laboratory identification number/test report number	0051 / CS25-0122198-01
Harmonized technical specification	EN 16510-2-1:2022
Load bearing capacity (kg)	70/ 70
Minimum distance to combustible materials - bottom dB [mm]	0/ 0
Minimum distance to combustible materials - floor in front dF [mm]	0/ 0
Minimum distance to combustible materials - distance to ceiling dC [mm]	750/ 750
Minimum distance to combustible materials - distance to rear dR [mm]	250/ 250
Minimum distance to combustible materials - left side dS_1 [mm]	1100/ 1100
Minimum distance to combustible materials - right side dS_2 [mm]	250/ 250
Minimum distance to combustible materials - left side radiation area dL_1 [mm]	400/ 400
Minimum distance to combustible materials - right side radiation area dL_2 [mm]	0/ 0
Minimum distance to adjacent combustible materials (e.g. furniture) dP [mm]	1000/ 1000
Material type and material thickness of the thermal insulation	-/-
CO at 13% O2 at nominal heat output [mg/Nm ³]	≤ 1500/397
NOX at 13% O2 at nominal heat output [mg/Nm ³]	≤ 200/79
OGC at 13% O2 at nominal heat output [mg/Nm ³]	≤ 120/18
Particulate matter (PM) at 13% O2 at nominal heat output [mg/Nm ³]	≤ 40/8
CO at 13% O2 at part load heat output [mg/Nm ³]	-/-
NOX at 13% O2 at part load heat output [mg/Nm ³]	-/-
OGC at 13% O2 at part load heat output [mg/Nm ³]	-/-
Particulate matter (PM) at 13% O2 at part load heat output [mg/Nm ³]	-/-
Flue gas temperature at the nozzle at nominal heat output [°C]	278/ 235
Minimum delivery pressure at nominal heat output [Pa]	12/ 12
Flue gas mass flow at nominal heat output [g/s]	6.9/ 6.7
Flue gas temperature at part load heat output [°C]	-/-
Minimum flue draught at part load heat output [Pa]	-/-



DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



Slim 4.0 left Type 1 / Type 2

1. LEK no.	KO 0067
2. Model	Stove
3. Intended use	Space heating in residential buildings
4. Manufacturer	Austroflam GmbH Austroflam-Platz 1 A-4631 Krenglbach
5. Representative	-
6. System(s) for assessing and verifying the constancy of performance of the construction product	3

Flue gas mass flow at part load heat output [g/s]	-/-
Fire safety for installation to the chimney	T400 G/T400 G
Nominal room heat output [kW]	6.5/ 8.1
Nominal water heat output [kW]	-/-
Efficiency at nominal heat output [%]	79.3/ 86.8
Partial load room heat output [kW]	-/-
Partial load water heat output [kW]	-/-
Efficiency at at part load heat output [%]	-/-
Space heating annual use efficiency [%]	69.3/ 76.8
Energy efficiency index (EEI)	105/ 116
Energy efficiency class	A/A+
Auxiliary power consumption at nominal heat output [kW]	-/-
Auxiliary power consumption at minimum heat output [kW]	-/-
Auxiliary power consumption in standby condition [kW]	-/-
Environmental sustainability	NPD/NPD

The performance of the aforementioned product corresponds to the declared performance(s). The above-mentioned manufacturer is solely responsible for the preparation of this declaration of performance in accordance with Regulation (EU) No. 305/2011.

Krenglbach, 02/12/2025


Andreas Schönfeld
Managing Director